

SECTION 4

ELECTRICAL EQUIPMENT

(Product Group - 500)

Fans and Smoke Alarms	148
Battery Supplies	149 - 150
Narva Electrical Fittings	162 - 165
Power Inlets and Outlets	166 - 169, 172
Power Points & Switches	166 - 172
Electrical Leads	169 - 171
CMS Equipment	170 - 172
15amp-10amp Adaptors	172 - 173
NARVA Accessory Sockets	174
Solar Panels	175 - 176
Tyre Inflators (Air Compressors)	176 - 177
Trailer Plugs and Sockets	177 - 179
Cable Ties	179
Caframo Fans	180 - 181
Briggs and Stratton Generators	182 - 183
Pressure Cleaners	184



LIGHTING EQUIPMENT

(Product Group - 500)

Lights and Lenses	151 - 153
Truck and Trailer Lighting	153 - 157
Led Bulbs	157 - 158
Reflectors	159
Sphere™ Wireless Lighting	160 - 161



GAS EQUIPMENT

(Product Group - 550)

Gas Regulators and Hoses	185 - 187
Gas Unions, Nuts and Valves	187 - 189
Gas Cylinders and Cradles	189 - 190
Gas Detector	190

GAS ACRONYMS

BSP	British Standard Pipe
BSPT	British Standard Pipe Tapered
NPT	National Pipe Thread
POL	Prest-O-Lite
SAE	Society of Automotive Engineers
M	This indicates that it is a male fitting
F	This indicates that it is a female fitting

For your own safety all gas fittings and equipment should be installed and checked by a qualified person.

550-00100 YELLOW GAS SEAL TAPE

Has a heat resistance of +200°C & a cold resistance of up to -20°C. Pressure resistant up to 2600kPa & is made of sintered PTFE (Poly Tetra Fluoro Ethylene).



Specifications

Dimensions: 12mm (W) x 10m (L)

LOXEAL 58-11 HIGH PRESSURE THREAD SEALANTS

Ideal for sealing threaded joints against gas, water, oils and other chemicals.

- > Anaerobic adhesive for the sealing of threaded metal to metal joints
- > Seals against gas, water, LPG, hydrocarbons, oils and other chemicals
- > High viscosity - won't run on thread
- > Sealing unaffected by shock/vibration within temperature range: -55°C to +150°C
- > Rapid cure time - functional in less than 3 hours
- > Water-safe & AGA-approved

550-00104 100ML TUBE



550-00106 250ML TUBE



REGULATORS

550-00298 GAS REGULATOR 2 STAGE (LOW PRESSURE)

Approved for use in portable applications such as outdoor cooking appliances that use a low pressure. Featuring a zinc construction, high and low 1/8" NPT pressure tap ports and a drip lip vent. Meets the RVIA, UL and NFPA test requirements.



Specifications

Capacity: 190,000BTU/hr (at 30 PSI inlet)

Inlet: 1/4" FNPT

Outlet: 3/8" FNP

550-00302 LPG (SINGLE STAGE) GAS REGULATOR

3.5kg/hr adjustable soft nose BBQ regulator 3/8" BSPF outlet.



550-00304 GAS CYLINDER 2 STAGE ADJ.160MJ REGULATOR



550-00306 GAS CYLINDER 2 STAGE ADJ.160MJ REGULATOR KIT-DUAL



550-00310 GAS REGULATOR 160MJ WITH BRACKET & PIGTAIL ADAPTOR



550-00312
GAS REGULATOR
160MJ MANUAL
CHANGE OVER &
BRACKET



550-00314
SINGLE GAS
CYLINDER
REGULATOR KIT

Single regulator with elbow, metal bracket, 3/8" adaptor with T point & flexible hose with hand wheel. Comes assembled.



550-00316
DUAL GAS CYLINDER
REGULATOR KIT

Manual change over regulator, metal bracket, 3/8" adaptor with T point & 2 flexible hoses with hand wheel. Comes assembled.



PIGTAIL

550-00320
COPPER PIGTAIL
POL X 1/4"
INVERTED FLARE
(750MM LONG)



550-00330
COPPER PIGTAIL
POL X 1/4"
INVERTED FLARE
(450MM)



GAS HOSES


550-00334
8MM S/S FLEXIBLE
HOSE 450MM

For single bottle kits (avalanche valve x 1/4" BSPM male)



550-00336
8MM S/S FLEXIBLE
HOSE 450MM

For double bottle kits (avalanche valve x inverted flare)



550-00337
8MM S/S FLEXIBLE
HOSE 600MM

For double bottle kits (avalanche valve x inverted flare)



550-00338
8MM S/S FLEXIBLE
HOSE 900MM

For double bottle kits (avalanche valve x inverted flare)



550-00340
S/S FLEXIBLE HOSE 450MM

with hand wheel for single bottle kit. (POL x 1/4" NPTM)



550-00341
S/S FLEXIBLE HOSE
600MM

with hand wheel for single bottle kit. (POL x 1/4" NPTM)



550-00344
S/S FLEXIBLE HOSE
450MM

with hand wheel for double bottle kit (POL x 5/16")



550-00345
S/S FLEXIBLE HOSE 600MM

with hand wheel for double bottle kit (POL x 5/16")

Class: F, 6mm, 2600Kpa



550-00349
S/S FLEXIBLE HOSE
3000MM

With Male Bayonet + Handle 3/8 Sae F




550-00350**VALVE & ADAPTER**

Manual changeover valve t/s regulator

**550-00360****MOUNTING BRACKET**

A universal regulator bracket (i.e. suits single, twin stage regulators)

**550-00370****SCREWS FOR MOUNTING BRACKET****550-00380****INVERTED FLARE STRAIGHT MALE UNION ADAPTER**

2 stage gas regulator. (1/4" NPTM x 1/4" female inverted flare)

**550-00390****INVERTED FLARE 90° ELBOW MALE UNION ADAPTOR**

2 stage gas regulator. (1/4" MNPT x 1/4" female inverted flare)

**550-00412****LPG AUTOMATIC SHUT-OFF VALVE & LEAK DETECTOR**

Gas safety shut-off valve automatically shuts off the flow of gas in case of a leak. Quick and easy to install the glow in the dark dial indicates when the gas level is low. Comes with a five year warranty.

**550-00500****GAS HOSE 3/8" BSPM X 3/8" SAEM X 300MM****550-00510****GAS HOSE - 6MM PVC, 5/16" SAE MF X 3/8" BSP M, 300MM**

For use with LPG (propane)

**Specifications**

Inlet: 5/16" SAE MF

Outlet: 3/8" BSP M

AGA Approval: 4237

Gas Hose Class (Max Working Pressure/Working Temp): C (2600kPa/-200C to +650C)

Hose Diameter: 6mm

550-00550**GAS HOSE 3/8" BSPM X 1/4" BSPF X 600MM****550-00560****GAS HOSE 3/8" BSPM X 1/4" BSPF X 900MM****550-00570****GAS HOSE 3/8" BSPM X 1/4" BSPF X 1200MM****550-00600****SAE MALE X BSP FEMALE UNION 5/16" X 1/4"****550-00602****SAE MALE X BSP FEMALE UNION 5/16" X 3/8"****550-00604****SAE MALE X BSP FEMALE UNION 3/8" X 1/4"****550-00606****SAE MALE X BSP FEMALE UNION 3/8" X 3/8"**

550-00608
SAE MALE X BSP FEMALE
UNION 3/8" X 1/2"



550-00626
SAE FLARE NUT 3/8"



550-00610
SAE MALE X SAE MALE
DOUBLE UNION
5/16" X 5/16"



550-00628
SAE REDUCING FLARE NUT
3/8" X 5/16"



550-00612
SAE MALE X SAE MALE
DOUBLE UNION 3/8" X 3/8"



550-00630
SAE 45° FLARE BRASS
FITTING, MALE UNION, 5/16
TUBE, 1/8 BSPT



550-00614
REDUCING UNION
3/8" X 5/16"



550-00632
SAE MALE X BSP TAPERED
MALE UNION 5/16" X 1/4"



550-00616
SAE MALE X SAE MALE DOUBLE
ELBOW 5/16" X 5/16"



550-00634
SAE 45° FLARE BRASS
FITTING, MALE UNION,
5/16 TUBE, 3/8 BSPT



550-00618
SAE ALL MALE 3-WAY TEE
CONNECTOR 5/16"



550-00636
SAE MALE X BSP TAPERED
MALE UNION 3/8" X 1/8"



550-00620
SAE ALL MALE 3-WAY TEE
CONNECTOR 3/8"



550-00638
SAE MALE X BSP TAPERED
MALE UNION 3/8" X 1/4"



550-00622
BSP MALE TAPERED X BSP
FEMALE ELBOW 1/4" X 1/4"



550-00640
SAE MALE X BSP
TAPERED MALE UNION
3/8" X 3/8"



550-00624
SAE FLARE NUT 5/16"



550-00642
SAE MALE X BSP MALE
TAPERED ELBOW 5/16"
X 1/4"



550-00644
SAE MALE X BSP MALE
TAPERED ELBOW 5/16" X 3/8"



550-00646
BALL VALVE BSP
FEMALE X BSP
FEMALE 1/4" X 1/4"



550-00648
FLARED BALL VALVE
5/16" X 5/16" SAE



550-00650
FLARED BALL VALVE 3/8" X
3/8" BSP



550-00652
FLARED BALL VALVE
1/2" X 1/2" BSP



550-00700
GAS TESTING NIPPLE
3/8" flare x 3/8" male



550-00710
GAS FLOOR SOCKET
FEMALE CHROME
 Manufactured from high quality
 brass and stainless steel. The
 unit is corrosion resistant
 and is approved to the AGA
 requirements. Chrome plated,
 with the inlet being a 1/2" BSP
 threaded connection. (7Kpa)



550-00711
DUST CAP T/S
CHROME PLATED
BAYONETS
 Dust cover to suit bayonet
 outlet.



550-00712
MALE BAYONET
SOCKET 1/4" BSP
 Comes with a 1/4" BSP
 male nipple for screw on
 attachment to a standard gas
 hose with compatible female
 union fittings.



GAS CYLINDERS

550-01000
MANCHESTER 9KG GRADE
2 GAS CYLINDER POL
 L/H Thread, No Gauge



550-01010
MANCHESTER 4KG GRADE
2 GAS CYLINDER POL
 L/H Thread, No Gauge



550-01302
STRAP RATCHET T/S GAS
BOTTLE
 Ratchet strap to suit gas bottles.



CRADLES

550-01052**CRADLE T/S 9KG
(GALVANISED)**

With a quick release mechanism.

**550-01062****CRADLE T/S 4KG
(GALVANISED)**

With a quick release mechanism.

**550-02010****12V GAS DETECTOR**

Can be installed in homes, motor homes, caravans and the like. It detects a gas leakage and triggers the alarm when the gas level reaches 10% of the LEL (Lowest Explosion Limit) in the air. 120H x 80W x 40D (mm)

**550-01300****GAS BOTTLE SLIDE
(WITH THUMB LOCKS)**

Made from mild steel, this slide holds x2 9kg gas bottles.

**Specifications**

Weight: 5.2kg

Dimensions: 656 x 280 x 285 (mm)